ABIMIG® A Lightweight Air-Cooled

200/300/400 Amp Torches

Ordering Instructions for Complete Torches

A	F	3	15	T	-	35	L1	S
Torch Model	Handle	Amperage	Cable Length	Nozzle		Wire Size	Back End	Handle

Torch Model

A - ABIMIG®

Handle

F - Fixed Neck

Amperage

2 - 200 Amp (255 Model)
3 - 300 Amp (355 Model)
4 - 400 Amp (415 Model)

Cable Length

10 Feet
15 Feet
20 Feet
25 Feet

Nozzle

T - Threaded

Handle

S - Short Trigger

Back End

E - Euro
L - Lincoln External gas
L1 - Lincoln 10
L2 - Lincoln Power MIG
L3 - Lincoln Powerfeeder 74/84/SP Series
HT - Hobart/Tweco
M - Miller Standard
M1 - Miller Multimatic[2]
X - No connector kit installed

Wire Size

35 - .035 Inches
45 - .045 Inches
52 - .052 Inches[1]
62 - .062 Inches[1]
78 - .078 Inches[3]
94 - .094 Inches[3]

[1] - 355 & 415 Models
[2] - 255 & 355 Models
[3] - 415 Models Only

ORD.0031 • REV 05-18 • © 2017 Alexander Binzel Corporation • Printed USA

Binzel S.A. DE C. V.
Municipio Pabellon de Arteaga 102
Valle De Aguascalientes, 20358
San Francisco de los Romo, Ags. Mexico
Phone: +52(499) 973.0133
Fax: +52(499) 973.1388
Email: info@binzel.com.mx

Alexander Binzel Corporation
650 Medimmune Ct., Suite 110
Frederick, MD 21703-8619
Phone: 1.800.542.4867
Fax: 1.301.846.4497
Email: customerservice@abicorusa.com

www.binzel-abicor.com