

ABIMIG® AT Lightweight Air-Cooled

200/300/400 Amp Torches

Ordering Instructions for Complete Torches

A	T	3	15	C	T -	3	L1	T
Torch Model	Handle	Amperage	Cable Length	Cable Type	Nozzle	Wire Size	Back End	Type
Torch Model A - ABIMIG®	Handle T - Rotating Neck	Amperage 2 - 200 Amp (255 Model) 3 - 300 Amp (355 Model) 4 - 400 Amp (415 Model)	Cable Length 10 Feet 15 Feet 20 Feet 25 Feet	Cable Type No letter = Light Weight C = Copper	Nozzle T - Threaded	Wire Size 35 - .035 Inches ¹ 45 - .045 Inches 52 - .052 Inches ² 62 - .062 Inches ² 78 - .078 Inches ³ 94 - .094 Inches ³ ¹ - 255 & 355 Models ² - 355 & 415 Models ³ - 415 Model Only	Back End E - Euro L - Lincoln External gas L1 - Lincoln 10, 74 & 84 Series L2 - Lincoln Power MIG HT - Hobart/Tweco M - Miller Standard M1 - Miller Multimatic ² X - No connector kit installed	Type T - Extended Trigger



Binzel S.A. DE C. V.
 Municipio Pabellon de Arteaga 102
 Valle De Aguascalientes, 20358
 San Francisco de los Romo, Ags. Mexico
 Phone: +52(499) 973.0133
 Fax: +52(499) 973.1388
 Email: info@binzel.com.mx

ABICOR BINZEL USA, Inc.
 650 Medimmune Ct., Suite 110
 Frederick, MD 21703-8619
 Phone: 1.800.542.4867
 Fax: 1.301.846.4497
 Email: customerservice@abicorusa.com

www.binzel-abicor.com