

xFUME® PRO Fume Extraction Torch

270/350/500 Amp Torches

Ordering Instructions for Complete Torches

XP	3	15	H - 35	L	L	S	
Model	Amp	Cable Length	Fume Nozzle (Shroud)	Wire Size	Cable Type	Back End	Trigger
XP - xFUME® PRO							Trigger S - Standard E - Extended
Amperage 2 - 270 Amp (Air-cooled) 3 - 350 Amp (Air-cooled) 5 - 500 Amp (Water-cooled)							Back End E - Euro HT - Tweco 4 L - Lincoln Ext Gas L1 - Lincoln 10, 74 & 84 Series L2 - Lincoln Power MIG M - Miller
Cable Length 15 - 15 Feet 20 - 20 Feet 25 - 25 Feet							Cable Type L - Lightweight (Standard) C - Full Copper (270+ 350A Only)
Fume Nozzle (Shroud) H - High-flow Threaded Tapered (Standard) HR - High-flow Threaded Reverse Suction (350/500A only) HS - High - Flow - Threaded Tapered Steel (350/500A only)							Wire Size .035 Inches .045 Inches .052 Inches .062 Inches (Water Cooled Only)



ABICOR BINZEL USA, inc.
650 Medimmune Court, Suite 110
Frederick, MD 21703
Phone: 800.542.4867
Fax: 301.846.4497
E-Mail: customerservice@abicorusa.com

www.binzel-abicor.com